

# Case Study – A Permeable Reactive Barrier for Denitrification

Watertech2014
Ryan Riess, M.Sc. P.Eng
April 12, 2014





#### **Overview**

- Site Background
- Theory
- Permeable Reactive Barrier Design
- Photos
- Data
- Conclusions





# Site Background

- Northern Alberta Site Active Fertilizer distribution facility
- Nitrate plume traveling south, shallow groundwater velocity approximately 1.5 metres per year
- Nitrate concentrations up to 1,400 mg/L in shallow groundwater traveling offsite






# Site Background

- Approximately 120 m south to nearest potable well from leading edge of plume
- Domestic Use Aquifer pathway eliminated
- Viterra wished to proactively address potential offsite liabilities
- Permeable Reactive Barrier (PRB) selected as a cost effective way to limit the nitrate flux traveling off-Site






# Site Background







### **Nitrification Theory**




- Requires Oxygen as electron acceptor
- Autotrophic, inorganic carbon (CO<sub>2</sub> and HCO<sub>3</sub><sup>-</sup>) for growth
- Reduces alkalinity





# **Denitrification Theory**



- Requires organic carbon
- Only occurs under anaerobic conditions
- Produces alkalinity





#### Literature review

- Wood chips effective for long term denitrification – more than 25 years
- Largest volume for a PRB
- Highest influent nitrate levels of 100 mg/L
- Efficiencies between 50 and 80 %
- Initial spike in downstream levels
- Downstream reductions double retention time






# **Design Considerations**


Influent nitrate Concentrations Up to 1,200 mg/L



Average ammonia influent concentrations 200 mg/L

Capped with 0.3 m clean clay





Length - 120 m

Volume - 960 m3

Pine wood chips

drainage Ditch to ensure saturation





# PRB Design

- Design life in excess of 20 years
- Hydraulic Conductivity of PRB was higher than surrounding soils based on slug tests
- Groundwater level an average of 0.8 metres below ground surface





# **PRB** Design

- Reasons to go offsite to the south:
  - No disruptions to operations
  - Further nitrification of ammonia from 500 to 200 mg/L
  - Presence of drainage ditch would ensure
     PRB remained saturated
  - Land was unproductive due to drainage issues





#### **PRB Preconstruction July 2011**







# PRB Design

- Benefits to adjacent landowner
  - Recycled metal, hauled debris away
  - Improved the drainage, landscaping of the area
  - "Reclaimed" about one acre of land,
     baled for the first time in summer 2013





#### **PRB Construction June 2012**







#### PRB Post Construction June 2012







#### PRB Post Construction May 2013








#### PRB Post Construction August 2013








#### **Results**






# Results – Dissolved Organic Carbon








# Results – Alkalinity








#### Results – Nitrate








# Results – Sulphate








#### Nitrate - Center







#### Nitrate – West Transect







#### Results

- PRB performing well
- Average Nitrate reduction of 95%
- Downstream nitrate concentrations have not yet shown a reduction – anticipated during 2014
- Sulphate reduction of 85% in east transect





# Acknowledgements

- Michael Edmonds, Viterra Inc.
- Crop Production Services Inc.
- PINTER & Associates Team





# THANK YOU

PINTER & Associates Ltd.

