


Tidal Implications for Contaminant Delineation in a Foreshore Environment

Erin Robson, M.Eng., P.Eng. Ian Mitchell, M.Sc., P.Geo.

SLR Consulting (Canada) Ltd.






Outline

- Site Description and History
- Previous Environmental Investigations
- Regulatory Framework and Literature Review
- Scope of Assessment
- Challenges
- Results of Hydrogeological Investigation
- Conclusions





Tide cycle - definitions

- **Intertidal Zone** the foreshore area between the low-tide and high-tide lines
- **Mixing Zone** the zone in which seawater and fresh landbased groundwater mix within the foreshore sediments of the intertidal zone
- Salinity refers to the measured specific conductivity of groundwater samples converted to salinity, in grams per litre, using the Practical Salinity Scale






Tide cycle - definitions


- **Sea Water Interface** the location of the interface between saline ocean water and the mixing zone
- **Tide Cycle** the rise and fall of sea levels due to the rotation of the Earth and the gravitational forces exerted by the Moon and the Sun. The tides occur with a period of approximately 12.5 hours.





Tide cycle - 4 stages

- **Ebb Tide** time within the tide cycle when the sea level is falling, exposing the intertidal zone (also called falling tide)
- Flood Tide time within the tide cycle when the sea level is rising, covering the intertidal zone (also called rising tide)




- Low Tide the point when the tide water has fallen to its lowest level within the tide cycle
- **High Tide** the point when the tide water has risen to its highest level within the tide cycle





Previous Investigations

- -Investigated in stages since mid-1990's
- -Irregular shaped dissolved diesel contaminant plume with "finger" into foreshore
- -Intermittent Light Non-Aqueous Phase Liquid (LNAPL), free-phase diesel (none on foreshore)
- -Uniform soils but potential preferential pathways and potential tidal influence not fully understood
- -Limited data on the foreshore








Objectives


Long term: Validate exposure concentrations for Risk Assessment and Risk Management and move towards site closure


Short term:


- -Evaluate and predict how groundwater chemistry changes under varying tidal conditions
- -Assess if contaminant loadings to the foreshore are greater during specific seasons and tides











British Columbia Regulatory Changes

- BC Ministry of Environment (MoE) has developed 3 new protocols relating to LNAPL and risk classification
- Under these new protocols the site would be classified as "high risk" based on two defined conditions under which LNAPL is considered to be mobile:
 - Measureable LNAPL is present over an inferred area of at least 10m²; and
 - Seasonal water table fluctuations exceed 1 metre
- Observational data can be collected to obtain an exemption from these conditions and thus lower the risk classification
- Lower risk classification = More flexible site management and less cost to client
- Theoretical LNAPL mobility assessment provides an additional line of evidence of LNAPL stability





Literature Review - Numerical Tidal Model

Quantitative analysis of seabed mixing and intertidal zone discharge in coastal aquifers, Roudrajit Maji and Leslie Smith


- Key concepts allowed understanding of tidal effects at our site
 - Groundwater discharge in intertidal >> submarine discharge
 - Majority of intertidal discharge is recirculated seawater
 - Localized and transient recharge and discharge sites due to density-driven convective circulation in the sediments
 - Spatial and temporal variation in contaminant loading rates can be significant
 - Contaminants discharge via a seepage face above the tide
 - Peak loading rates tend to occur mid tide on the falling tide






Hydrogeological Assessment

- Sediment porewater profiling
- Correlation of groundwater chemistry to tide cycles
- · Permeability / preferential pathway assessment



Scope of Intrusive Investigation




Challenges

 Time is of the essence when working in the intertidal zone!



Challenges

 Coarse sediments traditional hand-driven porewater profilers would not work!





 Drill rig would be required





Challenges

Even with a small rig, limited beach access called for creative solutions








Multilevel groundwater samplers



Extent of tidal influence inland






Salinity Contours (Seawater ~ 32 g/L)




Saltwater/Groundwater mixing zone







Multi-level groundwater sampler results Salinity Profiles




- Consistent throughout tide cycle
- Not affected by height of water
- Relatively consistent June vs Sept
- Salinity much lower at depth in Nov




EBB Tide







Plume Delineation in Intertidal - Soil






Results consistent with previous investigations




Seasonal LNAPL Distribution






- 20mm LNAPL within contaminant finger
- LEPHw indicative of LNAPL in central intertidal



Multi-level groundwater sampler results



LEPHw Profiles

- Consistent over tide cycle during Sept and Nov events
- Significant
 variability at depth
 during June event
- Concentrations not as high as adjacent hand dug pits or shallow monitoring wells











solutions for today's environment


Contaminant Trends

- Highest concentrations in June on the flood tide, in both the intertidal zone and the uplands (dry season and extreme low tides)
- Variability observed over the tide cycle with depth demonstrates the need for tidally correlated data
- Additional zone of dissolved contamination in central area
- Free-phase LNAPL (or concentrations indicative of) only observed in hand dug pits or monitoring wells which intercepted the water table - results from multi-level profiling points were lower





Permeability vs Contaminant distribution



Permeability vs. Grain size

TABLE E-1: HYDRAULIC CONDUCTIVITY VALUES

Test	Screen Interval (m)	Saturated Screen Length Stratigraphy	Hydraulic Conductivity (m/s)		
			Individual Tests	Well Averages	Geometric Mean
Upland Wells					
BH30	4.6 - 7.6	SAND	3.2 x 10 ⁻⁵	3.2 x 10 ⁻⁵	
BH37	4.6 - 7.6	SAND, some gravel	2.2 x 10 ⁻⁴	2.2 x 10 ⁻⁴	
BH50B Test 1	5.8 - 6.1	SAND, some gravel	7.1 x 10 ⁻⁵	7.0 x 10 ⁻⁵	
BH50B Test 2			6.9 x 10 ⁻⁵		
BH50B Test 3			6.9 x 10 ⁻⁵		
	•	Shallow Foreshore Wells]
BH55A	0.5 - 0.8	SAND, some gravel	8.3 x 10 ⁻⁵	8.3 x 10 ⁻⁵	1.1 x 10 ⁻⁴
Intermediate Foreshore Wells					1.1 X 10
BH54B	1.2 - 1.5	SAND, some gravel	3.7 x 10 ⁻⁵	3.7 x 10 ⁻⁵	
BH55B Test 1	1.2 - 1.5	SAND, some gravel	2.7 x 10 ⁻⁴	2.7 x 10 ⁻⁴	
BH55B Test 2			2.7 x 10 ⁻⁴		
Deep Foreshore Wells					
BH09-72	2.7 - 3.0	SAND and GRAVEL	3.0 x 10 ⁻⁵	3.0 x 10 ⁻⁵]
BH44B	2.7 - 3.0	SAND	3.1 x 10 ⁻⁴	3.1 x 10 ⁻⁴	
BH45C	4.2 - 4.5	SAND, some gravel	4.3 x 10 ⁻⁴	4.3 x 10 ⁻⁴	1


Notes:

m/s - metres per second






Effect of Tides on LNAPL Thicknesses





Inland Tidal Signal Strength and Lag Times



LNAPL Mobility Assessment

- Mobility was assessed at two locations where maximum LNAPL thickness was 0.32m and 0.21m respectively
- Local-scale mobility should occur only at LNAPL thicknesses exceeding 1.5m and 0.4m respectively, i.e., Local-scale LNAPL mobility is unlikely
- Plume-scale mobility calculated using the API LNAPL mobility assessment tool predicted that the plume is not likely mobile





Reading between the tides...

- Separate-phase LNAPL present on the east side of the intertidal zone
- Dissolved LEPHw indicative of LNAPL identified in the mid to western portion of the intertidal zone
- Peak LNAPL thicknesses following low tide
- Propagation of tidal signal and salinity gradient support potential preferential flow on the east side of the intertidal zone





Conclusions

- LNAPL mobility is low
- There are specific tide heights and seasons when monitoring and sampling provides "worst case" conditions for developing risk assessment exposure concentrations:
 - LNAPL and dissolved phase concentration monitoring at low water (low tide + lag time)
 - Contaminant loading rates best measured at mid tide on the falling tide, just after the LNAPL contaminant area is exposed by the receding tide water
 - Dry season is the most important period to collect data

References

- Aqui-Ver, Inc., 2004. "API Interactive LNAPL Guide". American Petroleum Institute.
- BC MoE, 2009. BC Ministry of Environment. Draft Protocol 16: Determining the Presence and Mobility of Nonaqueous Phase Liquids and Odorous Substances.
- Charbeneau, R.J. and Chiang, C.Y., 1995. "Estimation of Freehydrocarbon recovery from Dual Pump Systems, groundwater", 33(4): 627-634.
- Lenhard, R.J. and Parker, J.C., 1990. "Estimation of Free Hydrocarbon Volume from Fluid Levels in Monitoring Wells, groundwater", 28(1): 57-57.
- Maji, R and L. Smith, 2009. "Quantitative Analysis of Seabed Mixing and Intertidal Zone Discharge in Coastal Aquifers". Water Resour. Res., 45, W11401, doi:10.1029/2008WR007532.







Thank You SLR Consulting (Canada) Ltd.

Prepared for ESAA WaterTech 2010

